

FIBROL PETROLEUM HYDRO AW, HLP, HVI, HVLP

[Passenger car and heavy duty commercial motor vehicle]

SPECIFICATION OF FIBROL PETROLEUM HYDRO AW & HLP (GROUP-2)

FIBROL PETROLEUM HYDRO(GROUP-2)	AW 32	AW 46	AW68	AW 100	HLP 32	HLP 46	HLP 68	HLP 100
Viscosity cSt @ 40° C	32.8	46.8	68.5	101.4	32.7	45.6	68.4	99.8
Viscosity cSt @ 100° C	5.4	6.75	8.6	11.25	5.43	6.75	8.72	11.1
Viscosity Index,	97	97	96	96	110	108	108	104
Pour Point, °C,	-12	-12	-12	-12	-12	-12	-12	-12
Flash Point, °C,	210	212	212	216	215	220	220	228

SPECIFICATION OF FIBROL PETROLEUM HYDRO HVI & HVLP (GROUP-3)

FIBROL PETROLEUM HYDRO(GROUP-3)	HVI32	HVI46	HVI68	HVI 100	HVLP 32	HVLP 46	HVLP 68	HVLP 100
Viscosity cSt @ 40° C	32.7	46.7	68.7	100.7	32.7	45.6	68.4	99.8
Viscosity cSt @ 100° C	5.3	6.7	8.5	10.9	6.63	8.45	11.17	13.00
Viscosity Index,	164	145	148	127	164	164	156	130
Pour Point, °C,	-35	-33	-30	-24	-54	-45	-39	-33
Flash Point, °C,	220	232	236	248	250	232	240	258



FIBROL PETROLEUM

Website: www.fibrolpetroleum.com Email: fibrolpetroleum@gmail.com, CONTACT Number: 9890140990