

**FIBROL PETROLEUM FIBROL TEXTILE OIL FLP****[Textile Oil]****PROPERTIES TYPICAL TECHNICAL SPECIFICATION**

| SR.NO | CHARACTERISTICS                      | 100            | 150     | 220     | 320     | 460     | 680     |
|-------|--------------------------------------|----------------|---------|---------|---------|---------|---------|
| 1.    | Appearance                           | BRIGHT & CLEAR |         |         |         |         |         |
| 2.    | Colour ASTM                          | L 1.5          | L 1.5   | L 2.0   | L 2.0   | L 2.5   | L 3.0   |
| 3.    | Kinematic Viscosity c, cSt.          | 95-105         | 145-155 | 210-230 | 310-330 | 440-480 | 630-690 |
| 4.    | Viscosity Index, (Min.)              | 95             | 95      | 95      | 92      | 92      | 90      |
| 5.    | Flash Point, °C, (COC), (Min.)       | 218            | 226     | 234     | 240     | 240     | 240     |
| 6.    | Pour Point, °C, (Max)                | -9             | -6      | -6      | -3      | -3      | -3      |
| 7.    | Copper Corrosion 3hrs @100 C, (Max.) | 1a             | 1b      | 1b      | 1b      | 1b      | 1b      |

**FIBROL PETROLEUM**

Website: [www.fibrolpetroleum.com](http://www.fibrolpetroleum.com) Email: [fibrolpetroleum@gmail.com](mailto:fibrolpetroleum@gmail.com), CONTACT Number: 9890140990